

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.12.2020

Version number 3

Revision: 07.12.2020

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name **EPOXY BS 2000 FAST KOMP A**

Article number: 6934

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

**Application of the substance / the mixture** Coating

**Uses advised against** No further relevant information available.

#### 1.3 Details of the supplier of the safety data sheet

##### Manufacturer/Supplier:

Remmers GmbH

Bernhard-Remmers-Str. 13  
D-49624 Lönningen / Germany  
9QU

Tel.: +49(0)5432/83-0

Fax: +49(0)5432/3985

Remmers (UK) Limited

Unit 4 , Lloyds Court  
Manor Royal, Crawley – West Sussex RH10

fon +44 (0) 1293 594 010

fax +44 (0) 1293 594 037

##### Information department:

Product Safety department: Tel.: Steve Dunn Tel.: +44 (0) 1293 594 010

E-Mail: sales@remmers.co.uk

#### 1.4 Emergency telephone number:

during working hours:

+44 (0) 1293 594 010

sales@remmers.co.uk

Head Office Germany: Tel.: +49 (0)5432 83 187

info@remmers.de

after working hours: Tel.: +49 (0)171 21 34 091

24h-Transport Emergency Contact Phone Number:

within USA and Canada: 1-800-424-9300

outside USA and Canada: 001-703-527-3887

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

**Classification according to Regulation (EC) No 1272/2008**

Eye Dam. 1 H318 Causes serious eye damage.

#### 2.2 Label elements

**Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

##### Hazard pictograms



GHS05

**Signal word** Danger

##### Hazard-determining components of labelling:

Linseed oil polymer with bisphenol A, bisphenol A diglycidyl ether, diethylenetriamine, formaldehyde, glycidyl Ph ether and pentaethylenehexamine

(Contd. on page 2)

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.12.2020

Version number 3

Revision: 07.12.2020

Trade name **EPOXY BS 2000 FAST KOMP A**

(Contd. of page 1)

**Hazard statements**

H318 Causes serious eye damage.

**Precautionary statements**

P260 Do not breathe mist/vapours/spray.

P280 Wear protective gloves / eye protection / face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

**Additional information:**

EUH208 Contains reaction mass of 5-chloro-2- methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3- one (3:1), 2,2'-iminodiethylamine, 3,6,9-triazaundecamethylenediamine, 3,6,9,12-tetra-azatetradecamethylenediamine. May produce an allergic reaction.

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

**2.3 Other hazards****Results of PBT and vPvB assessment****PBT:** Not applicable.**vPvB:** Not applicable.**SECTION 3: Composition/information on ingredients****3.2 Mixtures****Description:** Mixture of the substances listed below with harmless additions.

<b>Dangerous components [% w/w]:</b>		
CAS: 13463-67-7 EINECS: 236-675-5 Index number: 022-006-00-2 Reg.nr.: 01-2119489379-17-XXXX	titanium dioxide ----- Carc. 2, H351	≥10-<20%
CAS: 68915-81-1	Linseed oil polymer with bisphenol A, bisphenol A diglycidyl ether, diethylenetriamine, formaldehyde, glycidyl Ph ether and pentaethylenehexamine ----- Eye Dam. 1, H318; Skin Irrit. 2, H315	≥5-<10%
CAS: 111-40-0 EINECS: 203-865-4 Index number: 612-058-00-X Reg.nr.: 01-2119473793-27-XXXX	2,2'-iminodiethylamine ----- Acute Tox. 2, H330; Skin Corr. 1B, H314; Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317; STOT SE 3, H335	≥0.1-≤0.5%
CAS: 112-57-2 EINECS: 203-986-2 Index number: 612-060-00-0	3,6,9-triazaundecamethylenediamine ----- Skin Corr. 1B, H314; Aquatic Chronic 2, H411; Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317	≥0.1-<0.25%
CAS: 4067-16-7 EINECS: 223-775-9 Index number: 612-064-00-2 Reg.nr.: 01-2119485826-22-XXXX	3,6,9,12-tetra-azatetradecamethylenediamine ----- Skin Corr. 1B, H314; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Sens. 1, H317	≥0.1-<0.25%
CAS: 55965-84-9 Index number: 613-167-00-5 Reg.nr.: 01-2120764691-48-XXXX	reaction mass of 5-chloro-2- methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3- one (3:1) ----- Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331; Skin Corr. 1B, H314; Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=100); Skin Sens. 1A, H317 Specific concentration limits: Skin Corr. 1C; H314: C ≥ 0.6 % Skin Irrit. 2; H315: 0.06 % ≤ C < 0.6 % Eye Dam. 1; H318: C ≥ 0.6 % Eye Irrit. 2; H319: 0.06 % ≤ C < 0.6 % Skin Sens. 1A; H317: C ≥ 0.0015 %	<0.00025%

(Contd. on page 3)

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.12.2020

Version number 3

Revision: 07.12.2020

Trade name **EPOXY BS 2000 FAST KOMP A**

(Contd. of page 2)

<b>Regulation (EC) No 648/2004 on detergents / Labelling for contents</b>
---

preservation agents (BENZISOTHIAZOLINONE)
---

**Additional information** For the wording of the listed hazard phrases refer to section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

**General information** When symptoms occur or in case of doubt, seek medical advice

**After inhalation** Take affected persons into the open air and position comfortably

**After skin contact** If skin irritation continues, consult a doctor.

**After eye contact** Rinse opened eye for several minutes under running water. Then consult doctor.

**After swallowing** Seek immediate medical advice.

### 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

### 4.3 Indication of any immediate medical attention and special treatment needed

symptomatic treatment

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

**Suitable extinguishing agents** Use fire fighting measures that suit the environment.

### 5.2 Special hazards arising from the substance or mixture

May be released in case of fire

Nitrogen oxides (NO<sub>x</sub>)

Formation of poisonous gases during heating or in fires.

### 5.3 Advice for firefighters

#### Protective equipment:

Wear self-contained breathing apparatus.

Wear full protective suit.

Put on breathing apparatus.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Put on breathing apparatus.

Wear protective equipment. Keep unprotected persons away.

**6.2 Environmental precautions:** Do not allow to enter the ground/soil.

### 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralising agent.

Dispose of contaminated material as waste according to item 13.

Ensure adequate ventilation.

### 6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Use only in well ventilated areas.

Ensure good ventilation/exhaust in workplaces.

Avoid the formation of aerosols.

**Information about protection against explosions and fires:** Keep breathing equipment ready.

### 7.2 Conditions for safe storage, including any incompatibilities

#### Storage

**Requirements to be met by storerooms and containers:** No special requirements.

**Information on storage in a common storage facility:** none

#### Further information about storage conditions:

Store container in a well ventilated position.

Protect from frost.

Keep container tightly closed.

(Contd. on page 4)

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.12.2020

Version number 3

Revision: 07.12.2020

Trade name **EPOXY BS 2000 FAST KOMP A**

(Contd. of page 3)

**7.3 Specific end use(s)** No further relevant information available.

## SECTION 8: Exposure controls/personal protection

**8.1 Control parameters**

<b>Components with limit values that require monitoring at the workplace:</b>	
<b>CAS: 13463-67-7 titanium dioxide</b>	
WEL	Long-term value: 10* 4** mg/m <sup>3</sup> *total inhalable **respirable
<b>CAS: 111-40-0 2,2'-iminodiethylamine</b>	
WEL	Long-term value: 4.3 mg/m <sup>3</sup> , 1 ppm Sk

**Additional information:** The lists that were valid during compilation were used as a basis.**8.2 Exposure controls****Appropriate engineering controls** No further data; see item 7.**Individual protection measures, such as personal protective equipment****General protective and hygienic measures**

Do not eat, drink or smoke while working.

Use skin protection cream for preventive skin protection.

Keep away from food, beverages and animal feed.

Immediately remove soiled, saturated clothing.

Wash hands before pauses and after work.

Do not inhale gases / vapours / aerosols.

Avoid contact with eyes and skin.

The following indication regarding the personal protective equipment are to be considered as suggestions. The selection of the necessary personal protective equipment is to be evaluated by the employer depending on the types of operations and the local circumstances. If a risk assessment on-site shows that there is no risk for employees, the personal protective equipment is not required or the amount of the PPE can be adapted accordingly.

**Respiratory equipment:**

Not necessary if room is well-ventilated.

Only use ambient air independent respiratory equipment in pits, shafts and silos!

In case of brief exposure or low pollution load, use respiratory protection equipment with filter. In case of intensive or longer exposure, use self-contained respiratory protection equipment.

**Hand protection**

Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

**Material of gloves**

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

**Penetration time of glove material**

The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

**Eye/face protection** Tightly sealed safety glasses.**Body protection:** Protective work clothing.

## SECTION 9: Physical and chemical properties

**9.1 Information on basic physical and chemical properties****General Information****Colour:**

According to product specification

**Odour:**

Amine-like

(Contd. on page 5)

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.12.2020

Version number 3

Revision: 07.12.2020

Trade name **EPOXY BS 2000 FAST KOMP A**

(Contd. of page 4)

<b>Odour threshold:</b>	Not determined.
<b>Melting point/freezing point:</b>	Not determined
<b>Boiling point or initial boiling point and boiling range</b>	Not determined
<b>Flammability</b>	Not applicable.
<b>Lower and upper explosion limit</b>	
<b>Lower:</b>	Not determined.
<b>Upper:</b>	Not determined.
<b>Flash point:</b>	>105 °C
<b>Decomposition temperature:</b>	Not determined.
<b>pH</b>	Not determined.
<b>Viscosity:</b>	
<b>Kinematic viscosity</b>	Not determined.
<b>dynamic at 20 °C:</b>	1,500 mPas
<b>Solubility</b>	
<b>Water:</b>	Not miscible or difficult to mix
<b>Partition coefficient n-octanol/water (log value)</b>	Not determined.
<b>Vapour pressure at 20 °C:</b>	23 hPa
<b>Density and/or relative density</b>	
<b>Density at 20 °C:</b>	1.33 g/cm <sup>3</sup>
<b>Relative density</b>	Not determined.
<b>Vapour density</b>	Not determined.
<b>9.2 Other information</b>	
<b>Appearance:</b>	
<b>Form:</b>	Fluid
<b>Important information on protection of health and environment, and on safety.</b>	
<b>Ignition temperature:</b>	not applicable
<b>Explosive properties:</b>	Product is not explosive.
<b>Solvent separation test</b>	< 3 %
<b>Organic solvents:</b>	0.0 %
<b>VOC EU</b>	0.0 g/l
<b>Change in condition</b>	
<b>Evaporation rate</b>	Not determined.
<b>Information with regard to physical hazard classes</b>	
<b>Explosives</b>	Void
<b>Flammable gases</b>	Void
<b>Aerosols</b>	Void
<b>Oxidising gases</b>	Void
<b>Gases under pressure</b>	Void
<b>Flammable liquids</b>	Void
<b>Flammable solids</b>	Void
<b>Self-reactive substances and mixtures</b>	Void
<b>Pyrophoric liquids</b>	Void
<b>Pyrophoric solids</b>	Void
<b>Self-heating substances and mixtures</b>	Void
<b>Substances and mixtures, which emit flammable gases in contact with water</b>	Void
<b>Oxidising liquids</b>	Void
<b>Oxidising solids</b>	Void
<b>Organic peroxides</b>	Void
<b>Corrosive to metals</b>	Void
<b>Desensitised explosives</b>	Void

## SECTION 10: Stability and reactivity

**10.1 Reactivity** No further relevant information available.

(Contd. on page 6)

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.12.2020

Version number 3

Revision: 07.12.2020

Trade name **EPOXY BS 2000 FAST KOMP A**

(Contd. of page 5)

**10.2 Chemical stability****Thermal decomposition / conditions to be avoided:**

No decomposition if handled and stored according to specifications.

**10.3 Possibility of hazardous reactions** Exothermic reaction with acids**10.4 Conditions to avoid** No further relevant information available.**10.5 Incompatible materials:** Acids**10.6 Hazardous decomposition products:** Nitrous vitriol gases**SECTION 11: Toxicological information****11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008****Acute toxicity:** Based on available data, the classification criteria are not met.**LD/LC50 values that are relevant for classification:** No further relevant information available.**Skin corrosion/irritation:** Based on available data, the classification criteria are not met.**Serious eye damage/irritation:**

Causes serious eye damage.

**Sensitisation:** Based on available data, the classification criteria are not met.**Germ cell mutagenicity:** Based on available data, the classification criteria are not met.**Carcinogenicity:** Based on available data, the classification criteria are not met.**Reproductive toxicity:** Based on available data, the classification criteria are not met.**STOT-single exposure:** Based on available data, the classification criteria are not met.**STOT-repeated exposure:** Based on available data, the classification criteria are not met.**Aspiration hazard:** Based on available data, the classification criteria are not met.**11.2 Information on other hazards****Endocrine disrupting properties**

None of the ingredients is listed.

**SECTION 12: Ecological information****12.1 Toxicity****Aquatic toxicity:** No further relevant information available.**12.2 Persistence and degradability** No further relevant information available.**12.3 Bioaccumulative potential** No further relevant information available.**12.4 Mobility in soil** No further relevant information available.**12.5 Results of PBT and vPvB assessment****PBT:** Not applicable.**vPvB:** Not applicable.**12.6 Endocrine disrupting properties**

For information on endocrine disrupting properties see section 11.

**12.7 Other adverse effects****Additional ecological information:****General notes:** Do not allow product to reach ground water, bodies of water or sewage system.**SECTION 13: Disposal considerations****Recommendation**

The given refuse codes are recommendations based upon the intended use of the product. Because of special use and disposal conditions at the user's, other codes may apply under other conditions.

**European waste catalogue**

20 01 27\* | paint, inks, adhesives and resins containing hazardous substances

**Uncleaned packaging:****Recommendation:** Disposal must be made according to official regulations.**SECTION 14: Transport information****14.1 UN number or ID number****ADR, IMDG, IATA** Void**14.2 UN proper shipping name****ADR, IMDG, IATA** Void

(Contd. on page 7)

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.12.2020

Version number 3

Revision: 07.12.2020

Trade name **EPOXY BS 2000 FAST KOMP A**

(Contd. of page 6)

<b>14.3 Transport hazard class(es)</b>	
<b>ADR, ADN, IMDG, IATA Class</b>	Void
<b>14.4 Packing group</b>	
<b>ADR, IMDG, IATA</b>	Void
<b>14.5 Environmental hazards:</b>	
<b>Marine pollutant:</b>	No
<b>14.6 Special precautions for user</b>	Not applicable.
<b>14.7 Maritime transport in bulk according to IMO instruments</b>	Not applicable.
<b>Transport/Additional information:</b>	Not a hazardous good according to the above regulations.
<b>UN "Model Regulation":</b>	Void

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Directive 2012/18/EU

**Named dangerous substances - ANNEX I** None of the ingredients is listed.

**REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3

**15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## SECTION 16: Other information

Delivery specifications are found in the respective Technical Information Sheets.

This data is based on our present state of knowledge. However, it does not constitute a guarantee for any specific product features and does not establish a legally valid contractual relationship.

### Relevant phrases

H301 Toxic if swallowed.

H302 Harmful if swallowed.

H311 Toxic in contact with skin.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H330 Fatal if inhaled.

H331 Toxic if inhaled.

H335 May cause respiratory irritation.

H351 Suspected of causing cancer.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

**Classification according to Regulation (EC) No 1272/2008** Calculation method

**Department issuing data specification sheet:** Product Safety department / EHS

**Version number of previous version:** 2

### Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

(Contd. on page 8)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 07.12.2020

Version number 3

Revision: 07.12.2020

**Trade name EPOXY BS 2000 FAST KOMP A**

(Contd. of page 7)

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 3: Acute toxicity - oral – Category 3

Acute Tox. 4: Acute toxicity - oral – Category 4

Acute Tox. 2: Acute toxicity - inhalation – Category 2

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1

Skin Sens. 1A: Skin sensitisation – Category 1A

Carc. 2: Carcinogenicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2